LC Fiber Optic Adapters



specifications

LC fiber optic adapters with integrated panel retention clips are TIA/EIA-604 FOCIS-10 compatible. Each LC simplex adapter shall connect one LC connector pair in one module space. Each LC duplex adapter shall connect two LC connector pairs in one module space.





technical information

Standards requirements: TIA/EIA-604 FOCIS-10 compatible; exceeds TIA/EIA-568-B.3 requirements:				
Split sleeve material:	eve material: Zirconia ceramic (required for singlemode applications)			
Insertion loss:	.1dB average (multimode and singlemode); supports the performance of FOCIS-10 compliant connectors/patch cords			
Return loss:	Supports singlemode (>40dB for SPC and >55dB for UPC) and multimode (>20dB) connector polish performance			

key features and benefits

Integrated panel retention clips	No metal clips to become bent, damaged or lost; simplex adapter clips automatically adjust for FOCIS-10 compliant panel thickness variations for improved mounting
Superior weld strength	Provides a more durable product under stress for improved reliability and increased life
Short flange design	Improved modularity and higher density usage
Adapters available in Mini-Com® Modules	System flexibility; modules are interchangeable within Mini-Com Outlets, Boxes, and Patch Panels
Modules available in multiple colors	Allows color-coding for network segregation

applications

LC Fiber Optic Adapters can be used with Mini-Com Modules, Patch Panels, and Surface Mount boxes for a complete fiber solution. LC adapters provide a rugged solution for LAN, SAN, public networks, and fiber-to-the desk applications. The high density 1.25mm ferrules double the port density compared to SC adapters. The HDCRT Connector Removal Tool can be used to simplify removal of connectors in high-density applications. Panduit also offers a full line of enclosures, cassettes, and panels that are pre-assembled with LC adapters.

LC Fiber Optic Adapters

Duplex MM: FADSLCZEI-L FADSLCZAQ-L

Duplex SM: FADSLCZBU-L

FADSLCZAG-L

L = Bag of 50 adapters; 100 per carton

Mini-Com® LC Adapter Modules

Duplex MM:CMDSAQLCZBLDuplex SM:CMDSLCZBU*Duplex SM APC:CMDSAGLCZBL

HD Connector Removal Tool

For LC and SC: HDCRT

*also offered in EI, BL, IW.

BU = Blue EI = Electric Ivory

BL = Black

IW = International White

LC Fiber Optic Adapters

design information

LC Adapter Type	Description	Application Type
Sr./Sr. (Senior/Senior)	Has a FOCIS-10 senior adapter interface (without keyway) at each end. Both ends accept FOCIS-10 compatible senior LC connectors (non-keyed; spring loaded ferrules).	Typically used for patch panel and outlet applications, including behind the wall applications.

selection information


Sr./Sr. Part Number	Adapter Type	Split Sleeve Material	Adapter Color	Module Color	Average Insertion Loss	Return Loss
LC Adapters						
FADSLCZAQ-L	Multimode Duplex	Zirconia Ceramic	Aqua	-	.1dB	>20dB
FADSLCZAG-L	Duplex Singlemode APC		APC Green	-		>40dB
FADSLCZBU-L	Singlemode Duplex		Blue	-		
LC Adapter Modules	S					
CMDSAQLCZBL	Multimode Duplex		Aqua	Black	.1dB	>20dB
CMDSLCZBU	Singlemode Duplex	Zirconia Ceramic	Blue	Blue**		>40dB
CMDSAGLCZBL	Duplex Singlemode APC		APC Green	Black		

^{**}Blue LC Adapters are also available with Black (BL), Electric Ivory (El), and International White (IW) Modules


LC Duplex Adapter




Mini-Com® LC Adapter Module



Opticom® LC Duplex Fiber Adapter Panel



Opticom[®] QuickNet[™] Cassettes



HDCRT Connector Removal Tool



Dimensions are in inches. [Dimensions in brackets are metric].

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. Republic of Singapore Phone: 65.6305.7575 PANDUIT JAPAN Tokyo, Japan Phone: 81.3.6863.6000 PANDUIT LATIN AMERICA Guadalajara, Mexico Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

